

Advanced Settings

- Wireless
- LAN
- WAN**
- IPv6

Internet Connection

Dual WAN

Port Trigger

Virtual Server / Port Forwarding

DMZ

DDNS

WAN - Internet Connection

RT-AC68U provides Dual WAN support. Select Failover mode to use a secondary WAN for backup network and LoadBalance mode to optimize bandwidth, maximize throughput, minimize response time, and prevent data connection drops.

WAN index

WAN Type: WAN

Basic Config

WAN Connection Type: **PPPoE**

Enable WAN:

Enable NAT:

Enable UPnP: Yes No

[UPnP FAQ](#)

NEXT



Account Setting

User Name

Password

Show password

Idle Disconnect Time in seconds: Disconnect after time of inactivity (in seconds)

MTU

الرئيسية

MRU

Service Name

Access Concentrator Name

Additional pppd options

Quick Internet Setup

Firmware Version: **1.0.6.4** SSID: **ASUS**

General Log

Wireless Log

DHCP leases

Routing Table

Port Forwarding

DSL Log

Spectrum

General

Network Map

Guest Network

Traffic Manager

Parental control

Advanced Settings

Wireless

LAN

WAN

IPv6

Firewall

Administration

System Log

Network Tools

System Log - DSL Log

This page shows the detailed system's activities.

DSL Driver Version	FwVer:3.20.44.0_A_TC3087 HwVer:T14.F7_11.2
DSL Link Status	up
DSL Uptime	0 days 0 hours 4 minutes 5 seconds
DSL Modulation	ITU G.992.5(ADSL2PLUS)
Annex Mode	ANNEX_M
SNR Down	33.2 dB
SNR Up	30.7 dB
Line Attenuation Down	5.7 dB
Line Attenuation Up	7.2 dB
Data Rate Down	8192 kbps
Data Rate Up	1021 kbps
MAX Rate Down	26012 kbps
MAX Rate Up	2600 kbps
POWER Down	13.4 dbm
POWER Up	12.7 dbm

الرئيسية