

Advanced

- Basic
- ▼ Status
- ADSL Status
- WAN Statistics
- ARP Table
- DHCP Table
- System Log
- Firewall Log
- UPnP Portmap
- Quick Start
- Configuration

Status

▼ ADSL Status

Parameters

DSP Firmware Version	A2pB025f.d22k
DMT Status	No Defect
Operational Mode ▶	ADSL2+

Upstream	1300
Downstream	13249
SNR Margin(Upstream)	68
SNR Margin(Downstream)	63
Line Attenuation(Upstream)	178
Line Attenuation(Downstream)	345

Refresh

الرئيسية

Quick Start

▼ WAN Port (WAN > Wireless)

ADSL Line Is Ready.

Auto scan

Auto Manually

NEXT

Apply

Connection

Profile Port

ADSL

Protocol

PPPoE (RFC2516, PPP over Ethernet)

VPI/VCI

8 / 35

Username

isat@username.co.za

Password

•••••

Service Name

Authentication Protocol

Chap(Auto)

IP Address

0.0.0.0

(*0.0.0.0' means 'Obtain an IP address automatically')

Obtain DNS automatically

Enable

Primary DNS/Secondary DNS

196.43.42.190

196.43.46.190

NEXT

Apply

Save Config

Restart

Logout

Wireless (WAN > Wireless)

Parameters

WLAN Service Enable Disable

ESSID

ESSID Broadcast Enable Disable

Regulation Domain

Channel ID

Security Parameters

Security Mode

WPA Shared Key

Group Key Renewal seconds

NEXT

▼ WAN Port (WAN > Wireless)

Process finished

Success.

الرئيسية

The Quick Start process is finished. Your device has been successfully configured.