

Device Information

Firmware Version : 3.0.0 Build 110615 Rel.08523
MAC Address : d8:5d:4c:99:28:71

LAN

IP Address : 192.168.1.1
Subnet Mask : 255.255.255.0
DHCP Server : Enabled

WAN

PVC	VPI/VCI	IP Address	Subnet	GateWay	DNS Server	Encapsulation	Status
PVC0	0/35	N/A	N/A	N/A	N/A	Bridge	Down
PVC1	0/32	N/A	N/A	N/A	N/A	Bridge	Down
PVC2	1/32	N/A	N/A	N/A	N/A	Bridge	Down
PVC3	0/100	N/A	N/A	N/A	N/A	Bridge	Down
PVC4	8/35	N/A	N/A	N/A	N/A	Bridge	Down
PVC5	0/38	N/A	N/A	N/A	N/A	Bridge	Down
PVC6	0/33	0.0.0.0	0.0.0.0	0.0.0.0	0.0.0.0	PPPoE	Down

ADSL

ADSL Firmware Version : FwVer:3.11.2.175_TC3086 HwVer:T14.F7_6.0
Line State : Down
Modulation : N/A
Annex Mode : N/A

	Downstream	Upstream	
SNR Margin :	N/A	N/A	db
Line Attenuation :	N/A	N/A	db
Data Rate :	N/A	N/A	kbps
Max Rate :	N/A	N/A	kbps
POWER :	N/A	N/A	dbm
CRC :	N/A	N/A	

next

Quick Start

The Wizard will guide you through these following quick steps. Begin by clicking on **NEXT**.

Step 1. Choose your time zone

Step 2. Set your Internet connection

Step 3. Save your current ADSL Router configuration

next

NEXT

EXIT

Quick Start - ISP Connection Type

Select the Internet connection type to connect to your ISP. Click **NEXT** to continue.

Dynamic IP Address

Choose this option to obtain a IP address automatically from your ISP.

Static IP Address

Choose this option to set static IP information provided to you by your ISP.

PPPoE/PPPoA

Choose this option if your ISP uses PPPoE/PPPoA. (For most DSL users)

Bridge Mode

Choose this option if your ISP uses Bridge Mode.

next

BACK

NEXT

EXIT

Quick Start - PPPoE/PPPoA

Enter the PPPoE/PPPoA information provided to you by your ISP. Click **NEXT** to continue.

Username:

Password:

VPI: (0~255)

VCI: (1~65535)

Connection Type: 

next

BACK

NEXT

EXIT

Quick Start Complete !!

The Setup Wizard has completed. Click on **BACK** to modify changes or mistakes. Click **NEXT** to save the current settings.

الرئيسية

BACK

NEXT

EXIT

pvc4

Virtual Circuit : PVC0

Status : Activated Deactivated

VPI : 0 (range: 0~255)

VCI : 35 (range: 1~65535)

ATM QoS : UBR

PCR : 0 cells/second

SCR : 0 cells/second

MBS : 0 cells

ISP : Dynamic IP Address

Static IP Address

PPPoA/PPPoE

Bridge Mode

next

Encapsulation : 1483 Bridged IP LLC

SAVE

DELETE

- ISP : Dynamic IP Address
 Static IP Address
 PPPoA/PPPoE
 Bridge Mode

Service name :

Username :

Password :

Encapsulation : PPPoE LLC

Bridge Interface : Activated Deactivated

- Connection : Always On (Recommended)
 Connect On-Demand (Close if idle for minutes)
 Connect Manually

TCP MSS Option : TCP MSS(default: 1400) bytes

Get IP Address : Static Dynamic

Static IP Address :

IP Subnet Mask :

Gateway :

NAT : Enable

Default Route : Yes No

TCP MTU Option : TCP MTU(default: 1480) bytes

Dynamic Route : RIP1 Direction : Both

Multicast : Disabled

MAC Spoofing : Enabled Disabled

الرئيسية

Device Information

Firmware Version : 3.0.0 Build 110615 Rel.08523
 MAC Address : d8:5d:4c:99:28:71

LAN

IP Address : 192.168.1.1
 Subnet Mask : 255.255.255.0
 DHCP Server : Enabled

WAN

PVC	VPI/VCI	IP Address	Subnet	GateWay	DNS Server	Encapsulation	Status
PVC0	0/35	N/A	N/A	N/A	N/A	Bridge	Down
PVC1	0/32	N/A	N/A	N/A	N/A	Bridge	Down
PVC2	1/32	N/A	N/A	N/A	N/A	Bridge	Down
PVC3	0/100	N/A	N/A	N/A	N/A	Bridge	Down
PVC4	8/35	N/A	N/A	N/A	N/A	Bridge	Down
PVC5	0/38	N/A	N/A	N/A	N/A	Bridge	Down
PVC6	0/33	0.0.0.0	0.0.0.0	0.0.0.0	0.0.0.0	PPPoE	Down

ADSL

ADSL Firmware Version : FwVer:3.11.2.175_TC3086 HwVer:T14.F7_6.0
 Line State : Down
 Modulation : N/A
 Annex Mode : N/A

	Downstream	Upstream	
SNR Margin :	N/A	N/A	db
Line Attenuation :	N/A	N/A	db
Data Rate :	N/A	N/A	kbps
Max Rate :	N/A	N/A	kbps
POWER :	N/A	N/A	dbm
CRC :	N/A	N/A	

الرئيسية