

Setup

Setup

Wireless

Security

Access
Restrictions

Applications &
Gaming

Administration

Status

Basic Setup

DDNS

Advanced Routing

Internet Setup

Internet Connection Type
VC Settings

Encapsulation: RFC 2364 PPPoA
Multiplexing: LLC VC
Qos Type: UBR
Pcr Rate: cps
Scr Rate: cps
Autodetect: Enable Disable
Virtual Circuit: 8
VPI (Range 0-255): 0
35
VCI (Range 0-65535): 35
ADSL Modulation: MultiMode

PPPoA Settings

Username: username@daya.sy
Password: *****
 Connect on Demand: Max Idle Time 5 Minutes
 Keep Alive: Redial period 30 Seconds

Optional Settings
(required by some ISPs)

Host Name:
Domain Name:
MTU: Auto
Size: 1500

Network Setup

Router IP

Local IP Address: 192 . 168 . 1 . 1
Subnet Mask: 255 . 255 . 255 . 0

Network Address
Server Settings (DHCP)

DHCP Server: Enable Disable DHCP Relay
DHCP Server: . . .
Starting IP Address: 192 . 168 . 1 . 100
Maximum Number of
DHCP Users: 50
Client Lease Time: 0 minutes (0 means one day)
Static DNS 1:
Static DNS 2:
Static DNS 3:
WINS:

Time Settings

Time Zone: (GMT-08:00) Pacific Time (USA & Canada)
Time Interval: 3600 seconds
 Automatically adjust clock for daylight saving changes.

Save Settings

Cancel Changes

الرئيسية

Status

Setup

Wireless

Security

Access
RestrictionsApplications &
Gaming

Administration

Status

Gateway |

Local Network |

Wireless |

DSL Connection

DSL Connection

DSL Status:	Connecting
DSL Modulation Mode:	Not Trained
DSL Path Mode:	Not Trained
Downstream Rate:	0 kbps
Upstream Rate:	0 kbps
Downstream Margin:	0 db
Upstream Margin:	0 db
Downstream Line Attenuation:	0 db
Upstream Line Attenuation:	0 db
Downstream Transmit Power:	0
Upstream Transmit Power:	0

PVC Connection

Encapsulation:	RFC 2364 PPPoA
Multiplexing:	VC
Qos:	UBR
Pcr Rate:	0
Scr Rate:	0
Autodetect:	Enable
VPI:	0
VCI:	38
Enable:	Yes
PVC Status:	Down

Help...

الرئيسية

Refresh