

Setup

Advanced

Management

Status

Help

Setup

Wizard

Internet Setup  

Wireless

Local Network

Time and Date

Logout  

INTERNET SETUP

Choose "Add", "Edit", or "Delete" to configure WAN interfaces.

WAN SETUP

	VPI/VCI	VLAN ID	ENCAP	Service Name	Protocol	State	Status	Default Gateway	Action
<input checked="" type="checkbox"/>	8/35	0	LLC	pppoe_8_35_0_0	PPPoE	1	Disconnected	<input type="checkbox"/>	<input type="button" value="Connect"/>

Setup

Advanced

Management

Status

Help

Setup

Wizard

Internet Setup

Wireless

Local Network

Time and Date

Logout

INTERNET SETUP

1 This screen allows you to configure an ATM PVC identifier (VPI and VCI) and select a service category.

ATM PVC CONFIGURATION

2 VPI : 8 (0-255)

3 VCI : 35 (32-65535)

4 Service Category : UBR Without PCR

Peak Cell Rate : 0 (cells/s)

Sustainable Cell Rate : 0 (cells/s)

Maximum Burst Size : 0 (cells)

CONNECTION TYPE

5 Protocol : PPP over Ethernet (PPPoE)

6 Encapsulation Mode : LLC

802.1Q VLAN ID : 0 (0=disable, 1 - 4094)

اکبس ہون
انزول لتحت

6 → Encapsulation Mode: LLC
802.1Q VLAN ID : 0 (0=disable, 1 - 4094)

PPP USERNAME AND PASSWORD

7 → PPP Username : user@runnet.sy
8 → PPP Password :
9 → Confirm PPP Password :
Authentication Method: Auto
Dial-up mode : AlwaysOn
Inactivity Timeout : 60 (Seconds [0-65535])
10 → MTU : 1492 (128~1540)
Keep Alive :
Use Static IP Address :
IP Address :

finish

الرئيسية

NETWORK ADDRESS TRANSLATION SETTINGS

11 → Enable NAT :
12 → Enable WAN Service :
Service Category : pppoe_8_35_0_0

Apply Cancel

Setup

Advanced

Management

Status

Help

Status

Device Info

Wireless Clients

DHCP Clients

Logs

Statistics  

Route Info

Logout

DEVICE INFO

This information reflects the current status of your DSL connection.

LOCAL NETWORK & WIRELESS

Interface	Received				Transmitted			
	Bytes	Pkts	Errs	Rx drop	Bytes	Pkts	Errs	Tx drop
LAN1	730242	3802	0	0	723795	1473	0	0
ADN-4100	52644	1000	0	0	52644	147	0	0

INTERNET

Service	VPI/VCI	Protocol	Received				Transmitted				
			Bytes	Pkts	Errs	Drops	Bytes	Pkts	Errs	Drops	
pppoe_8_35_0_0	8/35	PPPOE									

ADSL

Mode:	G.dmt	
Type:	Fast	
Line Coding:	Enable	
Status:	SHOWTIME.	
	Downstream	Upstream
SNR Margin (dB):	39.2	31.0
Attenuation (dB):	11.5	6.0
Output Power (dBm):	8.5	11.5
Attainable Rate (Kbps):	8600	11.5
Rate (Kbps):	256	12.5
D (interleave depth):	1	1

-  3
-  4
-  5
-  6

الرئيسية

Setup

Advanced


Management

Status

Help

Setup

Wizard

Internet Setup 

Wireless

Local Network

Time and Date

Logout 

2

INTERNET SETUP

Choose "Add", "Edit", or "Delete" to configure WAN interfaces.

WAN SETUP

	VPI/VCI	VLAN ID	ENCAP	Service Name	Protocol	State	Status	Default Gateway	Action
<input checked="" type="checkbox"/>	8/35	0	LLC	pppoe_8_35_0_0	PPPoE	1	Disconnected	<input type="checkbox"/>	<input type="button" value="Connect"/>

Add

Edit 

Delete

NEXT 

3

Setup

Advanced

Management

Status

Help

Setup

Wizard

Internet Setup

Wireless

Local Network

Time and Date

Logout

INTERNET SETUP

1 This screen allows you to configure an ATM PVC identifier (VPI and VCI) and select a service category.

ATM PVC CONFIGURATION

2 → VPI : 8 (0-255)

3 → VCI : 35 (32-65535)

4 → Service Category : UBR Without PCR ▾

Peak Cell Rate : 0 (cells/s)

Sustainable Cell Rate : 0 (cells/s)

Maximum Burst Size : 0 (cells)

CONNECTION TYPE

5 → Protocol : PPP over Ethernet (PPPoE) ▾

6 → Encapsulation Mode : LLC ▾

802.1Q VLAN ID : 0 (0=disable, 1 - 4094)

اکبس ہون
نزول لتحت

6 → Encapsulation Mode: LLC
802.1Q VLAN ID : 0 (0=disable, 1 - 4094)

PPP USERNAME AND PASSWORD

7 → PPP Username : user@runnet.sy
8 → PPP Password :
9 → Confirm PPP Password :
Authentication Method: Auto
Dial-up mode : AlwaysOn
Inactivity Timeout : 60 (Seconds [0-65535])
10 → MTU : 1492 (128~1540)
Keep Alive :
Use Static IP Address :
IP Address :

NETWORK ADDRESS TRANSLATION SETTINGS

11 → Enable NAT :
12 → Enable WAN Service :
Service Category : pppoe_8_35_0_0

Apply Cancel

الرئيسية