

Interface

Quick Start

Interface Setup

Advanced Setup

Access Management

Maintenance

Status

Help

Internet

LAN

Wireless

ATM VC

Virtual Circuit : PVC4

Status : Activated Deactivated

VPI : 8 (range: 0~255)

VCI : 35 (range: 1~65535)



QoS

ATM QoS : UBR

PCR : 0 cells/second

SCR : 0 cells/second

MBS : 0 cells

Encapsulation

ISP : Dynamic IP Address

Static IP Address

PPPoA/PPPoE

Bridge Mode



PPPoE/PPPoA

Servicename :

Username : اسم المستخدم@aya.sy

Password : كلمة المرور

Encapsulation : PPPoE LLC

Bridge Interface : Activated Deactivated

Connection Setting

Connection : Always On (Recommended)

Connect On-Demand (Close if idle for minutes)

Connect Manually

TCP MSS Option : TCP MSS(default:1400) 1380 bytes

IP Address

Get IP Address : Static Dynamic

Static IP Address : 0.0.0.0

IP Subnet Mask : 0.0.0.0

Gateway : 0.0.0.0

NAT : Enable

Default Route : Yes No

TCP MTU Option : TCP MTU(default:1480) 1420 bytes

Dynamic Route : RIP2-B Direction : Both

Multicast : IGMP v2

Interface

Quick Start

Interface Setup

Advanced Setup

Access Management

Maintenance

Status

Help

Internet

LAN

Wireless

Access Point Settings

Access Point : Activated Deactivated
 Channel : UNITED STATES Auto Current Channel : 10
 Transmit Power : High
 Beacon Interval(ms) : 20 (range: 20~1000)
 RTS/CTS Threshold : 2347 (range: 1500~2347)
 Fragmentation Threshold(bytes) : 2346 (range: 256~2346, even numbers only)
 DTIM(ms) : 1 (range: 1~255)
 Wireless Mode : 802.11b+g+n



11n Settings

Channel Bandwidth : 20/40 MHz
 Extension Channel : above the control channel
 Guard Interval : AUTO
 MCS : AUTO

Multiple SSIDs Settings

SSID Index : 1
 Broadcast SSID : Yes No
 Use WPS : Yes No
 SSID : اسم الشبكة (الوايرليس)
 Authentication Type : WPA-PSK/WPA2-PSK



WPA-PSK/WPA2-PSK

Encryption : TKIP/AES
 Pre-Shared Key : كلمة المرور للوايرليس (8~63 ASCII characters or 64 hexadecimal characters)

WDS Settings

WDS Mode : On Off
 WDS Encryption Type : TKIP
 WDS Key : (8~63 ASCII characters or 64 hexadecimal characters)
 Mac Address #1 : 00:00:00:00:00:00
 Mac Address #2 : 00:00:00:00:00:00
 Mac Address #3 : 00:00:00:00:00:00
 Mac Address #4 : 00:00:00:00:00:00

Wireless MAC Address Filter

Active : Activated Deactivated
 Action : Allow Association the follow Wireless LAN station(s) association.
 Mac Address #1 : 00:00:00:00:00:00