

Quick Internet Setup

Internet Connection Dual WAN Port Trigger Virtual Server / Port Forwarding DMZ DDNS NAT Passthrough

2

WAN - Internet Connection



DSL-N12E_C1 supports several connection types to WAN (wide area network). These types beside WAN Connection Type. The setting fields differ depending on the connection type y

PVC Summary

PVC Unit	VPI	VCI	Protocol	Encapsulation Mode	QoS	Internet	IPTV
PVC 1	8	35	PPPoA / PPPoE	PPPoE LLC	ubr	<input checked="" type="checkbox"/>	

WAN Transfer Mode

Transfer Mode: ADSL WAN (ATM) 3

PVC unit: PVC 2 4

Enable? Yes No 5

PVC Settings

VPI: 0

VCI: 32

Service Category: UBR

PCR: 0

Basic Config

WAN Connection Type: PPPoA/PPPoE 6

IP version: IPv4 IPv4 / IPv6 IPv6



- General
- Network Map
- Guest Network
- Traffic Manager
- Parental Controls
- Advanced Settings
 - Wireless
 - LAN
 - WAN 1
 - IPv6
 - Firewall
 - Administration
 - System Log
 - Network Tools

VLAN ID (1 ~ 4094)

IP Universal Settings

Encapsulation Mode 7

MTU bytes (Default : 1492)



IPv4 Setting

Get the WAN IP automatically? Yes No

PPP Setting

PPP Username 8 8
 8 8

Password 9
 Show password

PPP Authentication

Connection type Always On (Recommended)
 Connect On-Demand (Close if idle for minutes)

TCP MSS Option bytes (0 means use default)

Host-Uniq (Hexadecimal)

Additional pppd options

Special Requirement from ISP

MAC Address

10

Firmware Version: 1.1.2.2_17-g00f2807 SSID: XXXXXXXXXX



Quick Internet Setup

LAN IP DHCP Server Route **IPTV** Switch Control



11

LAN - IPTV

The WAN port must connect to the internet when watch IPTV.

WAN Type

WAN Type ADSL WAN (ATM) 12

Basic Config

Enable multicast routing (IGMP Proxy) Enable 13

WAN Port PVC 2 14

UDP Proxy(Udpxy) 0 15

Apply 16

General

Network Map

Guest Network

Traffic Manager

Parental Controls

Advanced Settings

Wireless

LAN

WAN

IPv6

Firewall

Administration

System Log

Network Tools

Firmware Version: 1.1.2.2_17-g00f2807 SSID: [redacted]



Quick Internet Setup

General

Network Map

Guest Network

Traffic Manager

Parental Controls

Advanced Settings

Wireless

LAN

WAN

IPv6

Firewall

Administration

System Log

Network Tools

LAN IP DHCP Server Route IPTV Switch Control17

LAN - Route

This function allows you to add routing rules into DSL-N12E_C1. It is useful if you connect several routers behind DSL-N12E_C1 to share the same connection to the Internet.

Basic Config

Enable static routes Yes No

Static Route List (Max Limit : 10)

	<u>18</u>	<u>19</u>	<u>20</u>	<u>21</u>	<u>22</u>	<u>23</u>
likesyria	Network/Host IP	Netmask	Gateway	Metric	Interface	Add / Delete
	<u>10.237.239.0</u>	<u>255.255.255.0</u>	<u>10.237.239.1</u>	<u>1</u>	<u>WAN</u>	<u>+</u>
	<u>10.1.0.0</u> <i>protv</i>		<u>10.10.0.200</u>			

Apply 24