

Wizard

Local Network

Internet Setup

Wireless Setup

Time and Date

CHANNEL CONFIGURATION

This page is used to configure the parameters for the channel operation modes of your ADSL Modem/Router. Note : When connect type of PPPoE and PPPoA only is "Manual", the "Connect" and "Disconnect" button will be enable.

WAN PHYSICAL TYPE
WAN Physical Type: DSL WAN Ethernet WAN

DEFAULT ROUTE SELECTION
Default Route Selection: Auto Specified

CHANNEL CONFIGURATION
VPI: **VCI:** **Encapsulation:** LLC VC-Mux
Channel Mode: PPPoE **Enable NAPT:** **Enable IGMP:**
VLAN: Disable Enable **VLAN ID(1-4095):**
IP Protocol:
PPP Settings: User Name: **Password:**
Type: **Idle Time (min):**
WAN IP Settings: **Type:** Fixed IP DHCP **انزل للأسفل**
Local IP Address: **Remote IP Address:**
Netmask:
Helpful Hints...

When configuring the router to access the Internet, be sure to choose the correct **Channel Mode** from the list below.

Please take care when entering your **username** and **password** as these are case sensitive. The majority of connection issues are caused by incorrect **username** or **password** combinations.

Note: Be sure to restart the router for the new Internet Setting to take effect.

[More...](#)

Channel Mode: Bridge
Enable NAPT: **Enable IGMP:**
VLAN: Disable Enable **VLAN ID(1-4095):**

PPP Settings: **User Name:** **Password:**
Type: Continuous **Idle Time (min):**

WAN IP Settings: **Type:** Fixed IP DHCP
Local IP Address: **Remote IP Address:**
Netmask:

Default Route: Disable Enable Auto
Unnumbered

CURRENT WAN TABLE:

Select	Inf	Mode	VPI	VCI	Encap	NAPT	IGMP	DRoute	IP Addr	Remote IP	NetMask	User Name	Status	Edit
<input type="radio"/>	pppoe1	PPPoE	8	35	LLC	On	Off	On	10.1 13.6 5.99	82.1 37.2 00.3	255. 255. 255. 255	qsee moh @tar assu l.sy	Up	 

Internet Setting to take effect.

[More...](#)





Channel Mode: Enable NAPT: Enable IGMP:
VLAN: Disable Enable VLAN ID(1-4095):

PPP Settings: User Name: Password:
Type: Idle Time (min):

WAN IP Settings: Type: Fixed IP DHCP
Local IP Address: Remote IP Address:
Netmask:

Default Route: Disable Enable Auto
Unnumbered

CURRENT WAN TABLE:

Select	Inf	Mode	VPI	VCI	Encap	NAPT	IGMP	DRoute	IP Addr	Remote IP	NetMask	User Name	Status	Edit
<input type="radio"/>	pppoe1	PPPoE	8	35	LLC	On	Off	On	10.1 13.6 5.99	82.1 37.2 00.3	255. 255. 255.	qsee moh @tar assu l.sy	Up	 
<input type="radio"/>	pppoe2	PPPoE	0	32	LLC	On	Off	Off	10.1 13.6 5.99	82.1 37.2 00.3	255. 255. 255.	ayat v	Up	 

Internet Setting to take effect.

[More...](#)

PPP INTERFACE - MODIFY

This page is used for advanced PPP interface configuration.

PPP INTERFACE

Protocol: PPPoE
ATM VCC: 0/32
Login Name:
Password:
Authentication Method:
Connection Type:
Idle Time (s):
Bridge: Bridged Ethernet (Transparent Bridging)
 Bridged PPPoE (implies Bridged Ethernet)
 Disable Bridge
AC-Name:
Service-Name:
MTU (1-1500):
Static IP:
Source Mac address: (ex:00:E0:86:71:05:02)

- Advanced Wireless
- Access Control List
- Port Triggering
- Port Forwarding
- DMZ
- Parent Control
- Filtering Options
- DOS Settings
- DNS
- Dynamic DNS
- Network Tools
- Routing**
- NAT

ROUTING CONFIGURATION

This page is used to configure the routing information. Here you can add/delete IP routes.

HOST



Enable

Destination 10.237.239.0

Subnet Mask 255.255.255.0

Next Hop

Metric 1

Interface pppoe2

رقم القناة لازم يكون نفس رقم القناة التي تم انشاء اتصال ip-tv عليها



Add Route Update Delete Selected Show Routes

STATIC ROUTE TABLE

Select	State	Destination	Subnet Mask	NextHop	Metric	Itf
--------	-------	-------------	-------------	---------	--------	-----

Helpful Hints...

You can click [Show Routes](#) to show Current IP Routing Table.

[More...](#)

Channel Mode: Bridge
Enable NAPT:
Enable IGMP:

VLAN: Disable Enable
 VLAN ID(1-4095):

PPP Settings:
User Name:
Password:

Type: Continuous
Idle Time (min):

WAN IP Settings:
Type: Fixed IP DHCP





Local IP Address:
Remote IP Address:

Netmask:

Default Route: Disable Enable Auto

Unnumbered:

CURRENT WAN TABLE:

Select	Inf	Mode	VPI	VCI	Encap	NAPT	IGMP	DRoute	IP Addr	Remote IP	NetMask	User Name	Status	Edit
<input type="radio"/>	pppoe1	PPPoE	8	35	LLC	On	Off	On	10.1 13.6 5.99	82.1 37.2 00.3	255. 255. 255. 255	qsee moh @tar assu l.sy	Up	 
<input type="radio"/>	pppoe2	PPPoE	0	32	LLC	On	Off	Off	10.1 13.6 5.99	82.1 37.2 00.3	255. 255. 255. 255	ayat v	Up	 

Internet Setting to take effect.
[More...](#)