

> WAN

> Auto PVC

> ATM

> ADSL

LAN

WLAN



WAN Physical Type:

ADSL WAN  Ethernet WAN

Default Route Selection:

Auto  Specified

VPI:

0

VCI:

32

Encapsulation:

LLC

VC-Mux

Channel Mode:

PPPoE

Enable NAPT:

Enable IGMP:

IP Protocol:

Ipv4/Ipv6

PPP Settings:

User Name:

username@aya.iptv.sy

Password:

password

Type:

Continuous

Idle Time (min):

WAN IP Settings:

Type:

Fixed IP

DHCP

IP Address:

ISP Gateway:

|                         |   |                              |                            |
|-------------------------|---|------------------------------|----------------------------|
| <b>WAN IP Settings:</b> |   |                              |                            |
| Type:                   | <input checked="" type="radio"/> Fixed IP | <input type="radio"/> DHCP   |                            |
| IP Address:             | <input type="text"/>                      | ISP Gateway:                 | <input type="text"/>       |
| Subnet Mask:            | <input type="text"/>                      |                              |                            |
| Primary DNS Server:     | <input type="text"/>                      | Secondary DNS Server:        | <input type="text"/>       |
| Default Route:          | <input checked="" type="radio"/> Disable  | <input type="radio"/> Enable | <input type="radio"/> Auto |
| Unnumbered:             | <input type="checkbox"/>                  |                              |                            |

9

|                          |                                    |
|--------------------------|------------------------------------|
| <b>IPv6 WAN Setting:</b> |                                    |
| Address Mode:            | <input type="text" value="SlAAC"/> |



|                |                                   |
|----------------|-----------------------------------|
| IPv6 DNS Mode: | <input type="text" value="Auto"/> |
|----------------|-----------------------------------|

|                    |                                     |
|--------------------|-------------------------------------|
| DHCPv6 Mode:       | <input type="text" value="Auto"/>   |
| Request DHCPv6 PD: | <input checked="" type="checkbox"/> |

10

- Connect
- Disconnect
- Add
- Modify
- Delete
- Undo
- Refresh

هنا يجب الضغط على زر **MODIFY**

في القناة يلي تم تأسيسها لخدمة **ip-TV**

وتفعيل الخيار المبين  Bridged Ethernet (Transparent Bridging)

وبعدها الضغط على زر **OK**

#### PPP Interface - Modify

|                        |  |
|------------------------|--|
| Protocol:              | PPPoE  |
| ATM VCC:               | 0/32   |
| Login Name:            | <input type="text" value="username@aya.iptv.sy"/>  |
| Password:              | <input type="text" value="password"/>  |
| Authentication Method: | <input type="text" value="AUTO"/>  |
| Connection Type:       | <input type="text" value="Continuous"/>  |
| Idle Time (s):         | <input type="text" value="0"/>   |
| Bridge:                | <input checked="" type="radio"/> Bridged Ethernet (Transparent Bridging)<br><input type="radio"/> Bridged PPPoE (implies Bridged Ethernet)<br><input type="radio"/> Disable Bridge |
| AC-Name:               | <input type="text"/>   |
| Service-Name:          | <input type="text"/>   |

- WAN
- LAN
- LAN
- DHCP
- DHCP Static
- LAN IPv6
- WLAN



### LAN Interface Setup

This page is used to configure the LAN interface of your ADSL Router. Here you may change the setting for IP address, subnet mask, etc..

|                                       |   |
|---------------------------------------|---|
| Interface Name:                       | Ethernet1   |
| IP Address:                           | <input type="text" value="192.168.1.1"/>                              |
| Subnet Mask:                          | <input type="text" value="255.255.255.0"/>                            |
| <input type="checkbox"/> Secondary IP |   |
| IGMP Snooping:                        | <input type="radio"/> Disable <input checked="" type="radio"/> Enable |



**Apply Changes**

|                         |                               |
|-------------------------|-------------------------------|
| LAN Port:               | <input type="text" value=""/> |
| Link Speed/Duplex Mode: | <input type="text" value=""/> |

**Modify**

**ETHERNET Status Table:**

| Select                | Port | Link Mode        |
|-----------------------|------|------------------|
| <input type="radio"/> | LAN1 | AUTO Negotiation |

- > **Route**
- > **Static Route**
- > IPv6 Static Route
- > RIP

- ▾ **NAT**
- ▾ **QoS**
- ▾ **CWMP**
- ▾ **Port Mapping**
- ▾ **Others**



## Routing Configuration

This page is used to configure the routing information. Here you can add/delete IP routes.

|              |  |    |
|--------------|--|----|
| Enable:      | <input checked="" type="checkbox"/>        | 12 |
| Destination: | <input type="text" value="10.1.0.0"/>      |    |
| Subnet Mask: | <input type="text" value="255.255.255.0"/> | 13 |
| Next Hop:    | <input type="text"/>                       |    |
| Metric:      | <input type="text" value="1"/>             | 14 |
| Interface:   | <input type="text"/>                       | 15 |

[Add Route](#)
[Update](#)
[Delete Selected](#)
[Show Routes](#)

⚙ Static Route Table:

| Select | State | Destination | Subnet Mask | NextHop | Metric | Itf |
|--------|-------|-------------|-------------|---------|--------|-----|
|        |       |             |             |         |        |     |